

UniControl

Parking Heater Dashboard Control Panel for Professional Use



The UniControl is a dedicated dashboard control panel for all Webasto parking heaters. A rigid housing, bright TFT display and extra-large operating buttons especially focus on professional applications and increase convenience for the users. The control panel is ideal for all those who wish to have pre-set vehicle temperature at scheduled times.

Thanks to large TFT display, multifunctional button and self-explanatory user interface access to functions has never been easier. The display illumination can be adapted depending on the lighting in the passenger compartment.

UniControl allows quick selection of comfort heating levels and operation time. Eco, Normal or Boost functions are meant to deliver exceptional energy-savings for large air heaters or - if necessary - very quick heat-up times. The availability of the comfort functions depends on the installed heater, though.

With the built-in timer function you can pre-program start times for your heater, 7 days in advance. Simple menu navigation allows a quick creation of individual pre-selection times and heating/ventilation functions.

Key Benefits at a Glance:

- Easy selection of heating or ventilation modes
- Quick and intuitive operation thanks to a TFT display and multifunction button
- ON/OFF button with individual programmable presets
- Status indication via multicolored LED
- Adaptive display illumination
- Three adjustable comfort heating levels
- 7-day timer function, 3 presets per day
- Quick and easy dashboard installation thanks to DIN standardized holding frame
- Switching on the heater along with ignition
- ADR mode for hazardous material transport

For specific applications, UniControl can be programmed to automatically switch on the parking heater along with the vehicle's ignition.

ADR mode for transport of dangerous goods by road allows quick cool down of the heater after operation.



Truck

Light
Vehicles

Bus



Marine



Off-Highway

Special
Vehicles

UniControl

Technical Specifications

	UniControl
Operating time	10 – 120 minutes 5 min. increments continuous heating function (RV only)
Power supply (V DC)	12 / 24
Power consumption, stand-by (mA)	0.8
Operating temperature range (°C)	-40 to +70
Connection type	Analogue Switch Output / W-Bus
Dimensions (L x W x H) (mm)	30.6 x 88.6 x 41.6
Weight (g)	55
ECE approval number	E1 10R - 047319
CE Declaration of Conformity	2014 / 30 / EU; 2011/65/EU for further information see Declaration of conformity

Supported Webasto Heaters:

- Thermo Top Evo 4 / 5 / 5+
- Thermo Pro 50 Eco
- Thermo Pro 90
- Thermo Top Pro 120 / 150
- Air Top 2000 STC
- Air Top Evo 40 / 55

Scope of Delivery:

- UniControl
- Connector Cable
- QuickStart Guide